

SAFETY JOGGER

INDUSTRIAL

Medium

BESTBOY EW S3

BESTBOYEW3

Wide Leather Safety Shoes

Designed for diverse industries, Safety Jogger BESTBOY EW S3 combines SR slip resistance, oil resistance, antistatic safety, and lasting all-day comfort.

Upper	Suede Leather
Lining	Recycled Mesh
Footbed	SJ foam footbed
Midsole	Steel
Outsole	PU/PU
Toecap	Steel
Category	S3 / SRC
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
Sample weight	0.659 kg
Norms	ASTM F2413:2018 EN ISO 20345:2011



BLK



SND




Antistatic

Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm




Breathable leather upper

Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



Forefoot energy absorption

Forefoot energy absorption reduces the impact of jumps or running on the body of the wearer.



Oil & fuel resistant

The outsole is resistant against oil and fuel.



Removable insole

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.



SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.

SAFETY JOGGER
WORKS

HEAD-TO-TOE
PROTECTION



Proudly ranked in the top 1% by EcoVadis for sustainability.

ENGINEERED
IN EUROPE

www.safetyjogger.com

Industries:

Assembly, Automotive, Construction, Industry, Logistics

Environments:

Dry environment, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Suede Leather			
	Upper: permeability to water vapor	mg/cm ² /h	5.4	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	58	≥ 15
Lining	Recycled Mesh			
	Lining: permeability to water vapor	mg/cm ² /h	30.3	≥ 2
	Lining: water vapor coefficient	mg/cm ²	242	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	PU/PU			
	Outsole abrasion resistance (volume loss)	mm ³	40	≤ 150
	Outsole slip resistance SRA: heel	friction	0.29	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.34	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.14	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.23	≥ 0.18
	Antistatic value	MegaOhm	58.8	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
Toecap	Steel			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	19.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	22.5	≥ 14

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com