



# SAFETY JOGGER

PROFESSIONAL



## CARIN OB

**Practical design, adjustable to every foot**

The CARIN shoes provide all-day comfort and safety with their ESD technology and removable footbed. They are perfect for busy professionals seeking foot care without compromising on style.

Lining	Coolmax Mesh
Footbed	SJ Hybrid 5MM
Outsole	EVA/Rubber (NBR)
Category	OB / ESD, A, SRC, E
Size range	EU 34-43 / UK 2.0-9.0 / US 2.5-11.5 JPN 21.0-27 / KOR 225-280
Sample weight	0.235 kg
Norms	ASTM F2892:2018 EN ISO 20347:2012



FUX



LBL



LGN



LIC



WHT



### Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



### Coolmax® lining

Coolmax® technology was originally developed for athletes. The material transports moisture and sweat, so that the body stays dry. We found it extremely suitable for people who work hard for hours every day too.



### Removable insole

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.

**SAFETY JOGGER**  
WORKS

**HEAD-TO-TOE PROTECTION**



Proudly ranked in the top 1% by EcoVadis for sustainability.

**ENGINEERED IN EUROPE**

[www.safetyjogger.com](http://www.safetyjogger.com)

**Industries:**  
Catering, Cleaning, Food & beverages, Medical

**Environments:**  
Dry environment, Extreme slippery surfaces

**Maintenance instructions:**  
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Lining	<b>Coolmax Mesh</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	28.9	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	231.3	≥ 20
Footbed	<b>SJ Hybrid 5MM</b>			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	<b>EVA/Rubber (NBR)</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	111	≤ 150
	Outsole slip resistance SRA: heel	friction	0.46	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.52	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.14	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.19	≥ 0.18
	Antistatic value	MegaOhm	N/A	0.1 - 1000
	ESD value	MegaOhm	68	0.1 - 100
	Heel energy absorption	J	31	≥ 20

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



HEAD-TO-TOE  
PROTECTION



Proudly ranked in the  
top 1% by EcoVadis  
for sustainability.



www.safetyjogger.com