

# SAFETY JOGGER

## INDUSTRIAL

Light

## DESERT S1 P

### Stylish Steel Toe Boots


DESERT safety shoe with slipresistant grip for stability, steel toe protection, antistatic safety, breathable canvas comfort and posture support.

Upper	Cotton
Lining	Cotton
Footbed	SJ foam footbed
Midsole	Steel
Outsole	PU/PU
Toecap	Steel
Category	S1 P / SRC
Size range	EU 36-47 / UK 3.5-12.0 / US 4.0-13.0 JPN 22.5-31 / KOR 235-310
Sample weight	0.700 kg
Norms	ASTM F2413:2024 EN ISO 20345:2011




#### SJ Foam

Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.



#### SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



#### Steel midsole

Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.



#### Antistatic

Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm



#### Steel toecap

Robust metal support to protect the feet of the wearer against falling or rolling objects.



#### SJ-3-Fit

Optimized fit and wearer comfort by adjusting the width of a Safety Jogger shoe to personal needs.



011



043



117



MUL

SAFETY JOGGER  
WORKS

HEAD-TO-TOE  
PROTECTION



Proudly ranked in the top 1% by EcoVadis for sustainability.

ENGINEERED  
IN EUROPE

www.safetyjogger.com

**Industries:**  
Automotive, Construction, Logistics, Industry

**Environments:**  
Dry environment, Uneven surfaces

**Maintenance instructions:**  
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Cotton			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	3.3	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	31.6	≥ 15
Lining	Cotton			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	17.2	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	140.7	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	PU/PU			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	46	≤ 150
	Outsole slip resistance SRA: heel	friction	0.32	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.32	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.16	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.18	≥ 0.18
	Antistatic value	MegaOhm	123.7	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
Toecap	Steel			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	16	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	19	≥ 14

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



HEAD-TO-TOE  
PROTECTION



Proudly ranked in the  
top 1% by EcoVadis  
for sustainability.



www.safetyjogger.com