



# SAFETY JOGGER

## INDUSTRIAL



## G703

Flexible, mid-cut ESD safety shoe

Size range EU 38-47 / UK 5.0-12.0 / US 5.5-13.0  
JPN 24-31 / KOR 250-310

Sample weight 0.642 kg



BLK



### S3

S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.



### SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



### Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



### Water resistant Upper (WRU)

Prevents penetration of water if not permanently exposed to high levels.



### Steel toecap

Robust metal support to protect the feet of the wearer against falling or rolling objects.



### Heel energy absorption

Heel energy absorption reduces the impact of jumps or running on the body of the wearer.

### Industries:

Catering, Food & beverages, Uniform

### Environments:

Dry environment, Wet environment

### Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

**SAFETY  
JOGGER**  
WORKS

**HEAD-TO-TOE  
PROTECTION**



Proudly ranked in the  
top 1% by EcoVadis  
for sustainability.

**ENGINEERED  
IN EUROPE**

[www.safetyjogger.com](http://www.safetyjogger.com)