



# SAFETY JOGGER

PROFESSIONAL



Light

## JULINE OB


### Professional and stylish work pump

Juline is the ideal work pump for people who need a professional and stylish look without sacrificing comfort and safety. Juline has a slip-resistant outsole with extra cushioning and a water-resistant leather upper, so you can work with confidence and keep going all day long.

Upper	Synthetic Leather
Lining	Synthetic Leather
Footbed	Synthetic Leather
Outsole	Rubber (NBR)
Category	OB / SRA
Size range	EU 35-42 / UK 3.0-8.0 / US 5.5-10.5 JPN 21.5-26.5 / KOR 230-270
Sample weight	0.246 kg
Norms	EN ISO 20347:2012



BLK



#### Oxygrip / SJ Grip

Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.



#### SRA slip resistance

Slip resistance is one of the most important features of safety and occupational footwear. SRA slip resistant soles are tested on a ceramic tile with dilute soap solution.



#### Breathable upper

Increased moisture and temperature management for extended wearer comfort.

SAFETY  
JOGGER  
WORKS

HEAD-TO-TOE  
PROTECTION



Proudly ranked in the  
top 1% by EcoVadis  
for sustainability.

ENGINEERED  
IN EUROPE

[www.safetyjogger.com](http://www.safetyjogger.com)

Industries:

Catering, Uniform

Environments:

Dry environment, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	Synthetic Leather			
	Upper: permeability to water vapor	mg/cm² /h	3.1	≥ 0.8
	Upper: water vapor coefficient	mg/cm²	26.0	≥ 15
Lining	Synthetic Leather			
	Lining: permeability to water vapor	mg/cm² /h	33.0	≥ 2
	Lining: water vapor coefficient	mg/cm²	264	≥ 20
Footbed	Synthetic Leather			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	Rubber (NBR)			
	Outsole abrasion resistance (volume loss)	mm³	139	≤ 150
	Outsole slip resistance SRA: heel	friction	0.30	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.32	≥ 0.32
	Outsole slip resistance SRB: heel	friction	N/A	≥ 0.13
	Outsole slip resistance SRB: flat	friction	N/A	≥ 0.18
	Antistatic value	MegaOhm	N/A	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	N/A	≥ 20

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



HEAD-TO-TOE  
PROTECTION



Proudly ranked in the  
top 1% by EcoVadis  
for sustainability.



www.safetyjogger.com