

Medium


MODULO PURE S3S VMTG

MDLOPUVELM

Easy-to-Clean and Metal-Free Safety Shoes with Velcro Closure

Vegan mid-cut safety shoe with Lorica upper, recycled mesh lining, velcro closure, metal-free protection, and Tiger Grip outsole for extreme traction on wet, uneven surfaces.

| | |
|---------------|---|
| Upper | Lorica |
| Lining | Recycled Mesh |
| Footbed | SJ foam footbed |
| Midsole | Anti-puncture Textile |
| Outsole | Rubber (NBR) |
| Toecap | Nano Carbon |
| Category | S3S / SR, ESD, HI, CI, FO, HRO |
| Size range | EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315 |
| Sample weight | 0.640 kg |
| Norms | EN ISO 20345:2022+A1:2024 ASTM F2413:2024 |



Metal free

Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



Tiger Grip Technology

Outsoles with Tiger Grip technology are renowned for their slip resistance, ability to withstand wear and tear and excellent traction on different surfaces, even wet and uneven ones. They are crafted with an exclusive rubber compound and engineered with specific patterns and grooves to enhance grip and stability.



Vegan

Uses or contains no animal products.



Nano carbon toecap

Ultralight high-tech material, metalfree with no thermal or electrical conductivity.



Slip resistance (SR)

Replaces the previously used term of SRA+SRB=SRC. SR means the slip test has been executed on tiles contaminated with soap and with oil.



Heat resistant outsole (HRO)

The outsole resists high temperatures up to 300°C.



WHT



BLK

Industries:

Catering, Chemical, Cleaning, Food & beverages

Environments:

Extreme slippery surfaces, Warm surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20345 |
|---------|--|--------------|-----------------------------------|--------------|
| Upper | Lorica | | | |
| | Upper: permeability to water vapor | mg/cm² /h | 1.80 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm² | 17 | ≥ 15 |
| Lining | Recycled Mesh | | | |
| | Lining: permeability to water vapor | mg/cm² /h | 18.2 | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm² | 146.8 | ≥ 20 |
| Footbed | SJ foam footbed | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | Dry 25600 cycles/Wet 12800 cycles | 25600/12800 |
| Outsole | Rubber (NBR) | | | |
| | Outsole abrasion resistance (volume loss) | mm³ | 124 | ≤ 150 |
| | Basic Slip resistance - Ceramic + NaLS - Forward heel slip | friction | 0.38 | ≥ 0.31 |
| | Basic Slip resistance - Ceramic + NaLS - Backward forepart slip | friction | 0.45 | ≥ 0.36 |
| | SR Slip resistance - Ceramic + glycerin - Forward heel slip | friction | 0.23 | ≥ 0.19 |
| | SR Slip resistance - Ceramic + glycerin - Backward forepart slip | friction | 0.26 | ≥ 0.22 |
| | Antistatic value | MegaOhm | 57.1 | 0.1 - 1000 |
| | ESD value | MegaOhm | 69 | 0.1 - 100 |
| | Heel energy absorption | J | 32 | ≥ 20 |
| Toecap | Nano Carbon | | | |
| | Impact resistance toecap (clearance after impact 100J) | mm | N/A | N/A |
| | Compression resistance toecap (clearance after compression 10kN) | mm | N/A | N/A |
| | Impact resistance toecap (clearance after impact 200J) | mm | 17.0 | ≥ 14 |
| | Compression resistance toecap (clearance after compression 15kN) | mm | 23.0 | ≥ 14 |

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com