



SAFETY JOGGER

INDUSTRIAL



S032 S1 P

Upper	Textile
Lining	Mesh
Footbed	EVA, Mesh
Outsole	Rubber (NBR)
Category	S1 P / SRC
Size range	EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 JPN 21.5-31 / KOR 230-310
Sample weight	0.605 kg
Norms	ASTM F2413:2018 EN ISO 20345:2011



BEI



Heel energy absorption

Heel energy absorption reduces the impact of jumps or running on the body of the wearer.



S1P

You work in dry environments, no risk of water/liquid sprays, and you need protection for your toes, protection against perforation, and a good breathability? Then you need S1P safety footwear.



SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



Steel toecap

Robust metal support to protect the feet of the wearer against falling or rolling objects.



Breathable leather upper

Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.

Industries:

Automotive, Food & beverages, Logistics, Industry

Environments:

Dry environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

**SAFETY
JOGGER**
WORKS

**HEAD-TO-TOE
PROTECTION**



Proudly ranked in the
top 1% by EcoVadis
for sustainability.

**ENGINEERED
IN EUROPE**

www.safetyjogger.com