

**X530 EH SB**

X530

## ### ## ### ###(EH ## ##)

Safety Jogger X530# ### ##, ## ## # EH ## ##### ## ##  
## # ## #####. ## ## ## ## ##.

## ##	#### ## ##
## ##	####, 3D ##
##	SJ # ##
##	## ## ##
###	PU/##
Top	##
#####	SB / PS, SR, SC, LG, WR, E, ##, CI, FO, HRO
## ##	EU 35-50 / UK 3.0-14.0 / US 3.0-15.0 JPN 21.5-33.0 / KOR 230-330
## ##	0.783 kg
###	ASTM F2413:2018 EN ISO 20345:2022




BRN



### ## ##  
## #### ## ## ## # ## #####  
## ## ##### #####.



###  
#### ## ##### # ## ## ##### #####.




```
### #(EH)
## #(EH)# ## ##### ##### ##
#####. 2# ## ##### ##### ##
### #####.
```



```
## ##(LG)
#### ## # ## # ##### #### ## #####
# #### ##### #### #### #####.
```



### ##  
### ## 300°C# ### ## # ####.



```
##
## #### #### ## #### ##### ##
#####.
```

## ##:  
####, ##, ##, ##, ##

## ##:  
### ##, ### ## ##, ## ##

## ## ##:  
### ## ##### ##### ## ##### ## ##### ## #####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	#### ## ##			
	##: ### ##	mg/cm²/h	4.84	≥ 0.8
	##: ### ##	mg/cm²	45	≥ 15
## ##	####, 3D ##			
	##: ### ##	mg/cm²/h	4.4	≥ 2
	##: ### ##	mg/cm²	35.9	≥ 20
##	SJ # ##			
	###: ####(##/##)(###)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
###	PU/##			
	### #####(## ##)	mm³	125 (Density: 1.15)	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.41	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.37	≥ 0.36
	SR ## ## - ## + ##### - ##### ## ##	##	0.28	≥ 0.19
	SR ## ## - ## + ##### - ## ## ##	##	0.25	≥ 0.22
	### ## #	###	N/A	0.1 - 1000
	ESD #	###	N/A	0.1 - 100
	#### ## ##	J	42	≥ 20
Top	##			
	#### ## # (## # ##### 100J)	mm	N/A	N/A
	#### ## # (## # ## ## 10kN)	mm	N/A	N/A
	#### ## # (## # ## ## 200J)	mm	17.5	≥ 14
	#### ## # (## # ## ## 15kN)	mm	21.0	≥ 14

### ##:  
##### ## ##### ##### ##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED  
IN EUROPE

www.safetyjogger.com